



Europäisches Patentamt
European Patent Office
Office européen des brevets



Publication number:

0 657 201 A2

(12)

EUROPEAN PATENT APPLICATION

(21) Application number: **94119522.4**

(51) Int. Cl.⁶: **B01D 35/30**

(22) Date of filing: **09.12.94**

(30) Priority: **13.12.93 US 166226**

(43) Date of publication of application:
14.06.95 Bulletin 95/24

(84) Designated Contracting States:
DE ES FR GB IT

(71) Applicant: **STANADYNE AUTOMOTIVE CORP.**
92 Deerfield Road
Windsor
Connecticut 06095 (US)


(72) Inventor: **Janik, Leon P.**

879 North Street
Suffield,
Connecticut 06078 (US)
Inventor: **Maxwell, M. Craig**
8 Forest Drive
Colchester,
Connecticut 06415 (US)

(74) Representative: **Glawe, Delfs, Moll & Partner**
Patentanwälte
Liebherrstrasse 20
D-80538 München (DE)

(54) **Module for filter assembly base.**

(57) A filter assembly (10) employs a base (12) which mounts a disposable filter element cartridge (14). The cartridge (14) includes either a single stage or a dual stage filter system. The base (12) has custom and generic (20) structural members. Variations in base design are accommodated in the custom member, the generic member (20) having a generic design. The custom member is molded from polymeric material and requires no additional machining or treatment prior to use. This eliminates filter model specific shop fixtures and jigs, reducing costs and providing greater flexibility.



EP 0 657 201 A2

BG

Background of the Invention

This invention relates generally to devices for filtering and separating liquids. More particularly, the present invention relates to filters for removing foreign particles and separating water from fuel of the fuel supply system or lubricating oil of an internal combustion engine.

The absence of high standards of quality control in diesel fuel supplies dictates that an effective fuel filter be incorporated into the fuel supply system of a diesel engine. It is not uncommon for diesel fuel to have significant quantities of abrasive particles and water. The abrasive particles present the potential for permanent damage to components of the fuel injection pump. The abrasive particles can also adversely affect the performance of the pump by destroying the ability of the fuel injection pump to precisely meter and deliver fuel at high pressures. The presence of water in the diesel fuel supply can cause corrosion of engine components, and during freezing conditions, can result in interruption of the fuel injection system and/or seizure of moving components. Similarly, water and particulate matter in the lubricating oil must be removed to minimize wear of engine parts.

Commonly, filters employ a disposable filter cartridge which is replaced at pre-established intervals of filter usage. The cartridge is secured to a base assembly that is fixedly mounted to the engine header or some other fixed location. Variations between mounting locations and space constraints between different model engines and different manufacturers require a wide variety of filter designs.

Current filter assemblies to which the invention relates employ a base assembly principally composed of a metal casting. Such castings must be machined and treated before they are suitable for use. Machining and treatment machining and fixtures suitable for one filter design are commonly unsuitable or have limited use in other filter designs. Consequently, tooling costs are a significant component in the cost of the finished product. Additionally, production lines must change from one set of tooling to another when the line shifts production from one model to another. This process is time consuming, adding to production costs and limiting production flexibility.

Summary of the Invention

Briefly stated, the invention in a preferred form is a filter assembly wherein the base assembly comprises custom and generic structural members. Variations in filter base design are accommodated in the upper custom member, the lower generic member has a generic design. The custom mem-

ber is molded from polymeric material. The generic member may be molded polymeric material or cast metal. Molded polymeric material components require no additional machining or treatment prior to use, thereby eliminating the machining and treating jigs and fixtures and production line changeovers heretofore required.

In one embodiment the base is comprised of joined custom and generic structural members. The custom member comprises a central axial bore defined by an integral elongated sleeve-like conduit, an intermediate concentric sleeve-like conduit of reduced length, an outer locating ring and a base plate. The generic member comprises a base plate and an outer sleeve. The generic member base plate has an aperture for receiving the first and second conduits and the locating ring. Screws may be used to join the custom and generic member base plates. An end-cap seals the top of the custom member by means of a seal ring and/or a sonic weld, providing a fluid tight connection with respect to the upper cavity of the custom member.

The disposable filter cartridge is partially received within the generic member sleeve and is sealable with the first and second axial conduits which are partially received in the cartridge. The cartridge may include one or more filter elements. The flow path through the cartridge traverses through the first conduit, the filter elements and the second conduit. A retainer element is employed for locking the cartridge to the base.

An object of the invention is to provide a new and improved filter assembly.

Another object of the invention is to provide a new and improved filter assembly wherein variations in filter base design are accommodated by custom structural member made from molded polymeric material.

A further object of the invention is to utilize precision molding techniques and materials such that the polymeric base assembly components require no additional machining or treatment prior to use, thereby eliminating expensive machining and treatment jigs and fixtures and time consuming production line changeovers.

Other objects and advantages of the invention will become apparent from the drawings and the specification.

Brief Description of the Drawing

The present invention may be better understood and its numerous objects and advantages will become apparent to those skilled in the art by reference to the accompanying drawing wherein like reference numerals refer to like elements in the several figures and in which:

Figure 1 is an exploded view of a filter assembly in accordance with the present invention;

Figure 2 is a sectional view of the assembled filter assembly of Figure 1;

Figure 3 is a sectional view of the base portion of the fuel assembly Figure 2;

Figure 4 is a front view of the generic structural member of the fuel assembly base portion of Figure 3;

Figure 5 is a side view of the custom structural member of the fuel assembly base portion of Figure 3; and

Figure 6 is a top sectional view, partly in phantom, of the fuel assembly base portion custom structural member of Figure 5, said custom structural member being rotated 90° to the orientation of Figure 5.

Detailed Description of the Preferred Embodiment

With reference to the drawings wherein like numerals represent like parts throughout the several figures, a filter assembly in accordance with the present invention is generally designated by the numeral 10. Filter assembly 10 comprises a base 12 and a disposable filter cartridge 14. The filter assembly is especially adapted for incorporation into the fuel supply system or lubricating oil system of an internal combustion engine (not illustrated), such as a diesel engine, for removing particulate matter from the fuel or oil and for separating water from the fuel or oil. The base 12 is fixedly mounted to the engine header or other fixed location of the vehicle. Filter cartridge 14 is secured to the base by means of a retainer collar 16.

The base 12 forms an inverted cup-like receptacle which defines a lower receiving cavity for the upper portions of the disposable cartridge. The base 12 is comprised of joined custom 18 and generic 20 structural members. The custom structural member 18 is precision molded from polymeric material, wherein the cast member requires no additional machining or treating. Screws 40, snaps, etc. may be used to join the custom 18 and generic 20 members.

The molded custom member 18 comprises a central axial bore 22 defined by an elongated sleeve-like conduit 24, an intermediate concentric sleeve-like conduit 26 of reduced length, a coupling plate 38, an outer locating ring 30, and an upper circumferential lip 44. The upper lip 44 abuts the annular ring 52 of end-cap 50. The end-cap 50 is sealed to the custom member 18 by means of sonic/friction weld 66 to provide a fluid tight connection with respect to an upper cavity 56 of the base 12.

Conduits 24 and 26 provide generally co-axial fluid communication between the base and the disposable cartridge. An inlet passage 82 includes an inlet connector 27 at custom member side location for connection with a supply line (not shown). The inlet passage 82 provides fluid communication via the base upper cavity 56 from the axial central bore 22 defined by conduit 24. An outlet connector 33 at custom member side location connects with an outlet line (not shown) to provide fluid communication via passageway 34 from the axial fluid conduit 32 defined between the first and second conduits 24 and 26. Alternatively, the inlet connector 27 and the outlet connector 33 may be located at different locations on the custom member 18. Such location is determined by the particular design requirements and constraints of each type of vehicle. The inlet 82 and outlet 34 passageways may be a stepped-bore design, as shown in Figure 6, single bore, tapered bore, or other design as dictated by filter design requirements, mold design requirements and material requirements.

The custom member 18 may also include structures for an electric heater (not shown). An electrical connector 84 is connected to electrical posts 86 and 88. An electric heater is disposed in the base upper cavity 56 and connected to electrical posts 86 and 88 for heating the fuel or oil during cold conditions. Where no electric heater is required, the design shown in Figure 6 may be utilized and the electric heater omitted. Alternatively, the custom member design may omit the electric heater and the electrical connector 84 and electric posts 86 and 88.

The custom member 18 and the end-cap 50 are molded from an elastomeric material, for example Valox DR-48™, Ultradur B-4300-G4™, or RTP 1103™, that requires no additional machining or treatment prior to use. Use of such material eliminates the need for machining and treating jigs and fixtures and production line changeovers heretofore required to properly finish said parts.

The generic member 20, which may be cast from metal, comprises a coupling plate 36 having an aperture 48 for receiving the first and the second conduits 24 and 26 and the locating ring 30. An integral projecting bracket 42 for anchoring the filter base 12 to the engine projects transversely from the back of the generic member 20. The bracket 42 contains one or more slots 46 to facilitate mounting the base to the header or other appropriate structure of an internal combustion engine.

The disposable filter cartridge 14 comprises a can-like container 70 which is formed by a pair of lower and upper cup-like metal sections 72 and 74 which are joined along a circumferential roll seam 80. The truncated upper section 72 is a molded

member which includes a central axial opening. An upper sealing grommet 76 mounted at the opening diametrically seals against the outer conduit 26. The top surface of container section 72 is contoured to form an annular recess 77.

A filter element 78 which has a continuous fan-shaped pleated configuration is housed within the container 70. The filter element 78 axially extends approximately three quarters of the length of the container 70. The filter element 78 thus defines an interior axial chamber 66 and quasi-annular outer chamber 68. The filter element 78 is affixed with resin binders or other water coalescers so that as fuel or oil passes through the filter element 78, the water coalesces to form water droplets. A water barrier may also be employed. A sump 90 is formed at the bottom of the lower section 74 to collect water which separates from the fuel or oil. A drain valve 92 is disposed in the lower portion 74 of the cartridge for draining the water.

The lower end of the filter element 78 is engaged by a plate 102 which has a central port 104. A tubular structure 106, coaxial to the central port 104, engages the plate 102 and extends upward a part of the length of the interior axial chamber 66. The tubular structure 106 coaxially receives a lower portion of the inner conduit 24 wherein the vertical gap between the lower end of the outer conduit 26 and the upper exterior end of the tubular structure 106 defines a passage for the flow of fuel or oil out of the filter element 78 via the axial fluid conduit 32. A lower sealing grommet 108 mounted adjacent the upper end of the tubular structure 106 diametrically seals against the inner conduit 24.

Alternatively, the disposable cartridge may comprise dual filter elements having a continuous fan-shaped configuration.

The cartridge includes an annular recess 94. The annular recess 94 is located inwardly adjacent the roll seam 80. The retainer collar 16 includes a rim-like shoulder 100 for retentively engaging the roll seam 80.

The base generic member 20 includes a pair of integral outwardly projecting, diametrically disposed ramps 60 and 62. Each of the ramps ascends in spiral-like fashion in excess of 90° around the base. The upper ends of the ramps are beveled. Stops 64 are angularly spaced from the respective upper ends of the ramps. Spiral-like ramps 58 of the collar 16 are dimensioned and positionable for engagement with the ramps 60, 62 and stops 64 of the base, so that the collar ramps 58 slideably engage and ascend the generic member ramps 60, 62 upon alignment and angular rotation of the collar. The inclination angle of the upper surfaces of the generic member ramps and the underside surfaces of the collar ramps 58 are constant and substantially equal. The upper ramp

surfaces of the generic member ramps 60, 62 and the underside surface of the retainer collar ramps 58 engage along an extended substantially surface-to-surface interface. The locked position may be facilitated by the leading end of the collar ramps 58 engaging the stops 64 and engaging a detent.

Claims

1. A fuel filter assembly (10) having a base (12), a filter cartridge (14) mountable to the base (12) for filtering fuel, and a retainer (16) for retaining the filter cartridge (14) with the base (12), the base (12) having a fuel inlet (27), a fuel outlet (33), a first conduit (24) for interiorly defining a first axial passage, the first axial passage being in fluid communication with the inlet (27), a second conduit (26) for defining a second axial passage, the second axial passage being in fluid communication with the outlet (33), the filter cartridge (14) having at least one filter element (78), an end portion defining an axial opening for receiving the base first (24) and second (26) conduits, a first seal (76) for sealing the base second conduit (26) with the cartridge end portion, and defining a fuel path communicating with the base first axial passage, the base second axial passage and traversing the element (78), characterized by:

the base (12) comprising cooperative first, (18) and second (20) modules, said first module (18) having the inlet (27), the outlet (33), and the first (24) and second (26) axial conduits, said second module (20) being joined to said first module (16) and having an aperture (48) for receiving the first (24) and second (26) conduits.

2. The filter assembly of claim 1 characterized by said first module (18) further comprising locating means (30) for positioning the first (24) and second (26) conduits within said second module aperture (48).

3. The filter assembly of claims 1 and 2 characterized by an end-cap (50) mounted to said first module (18), said end-cap (50) defining a cavity (56).

4. The filter assembly of claim 3 characterized by said end-cap (50) and said first module (18) being connected by means of a weld.

5. The filter assembly of claims 1-4 characterized by said first (18) and second (20) modules each further comprising coupling plates (38, 36) and the base (12) further comprising

means for mounting (40) said first module coupling plate (38) to said second module coupling plate (36).

6. The filter assembly of claim 5 characterized by said mounting means (40) comprising at least one screw. 5
7. The filter assembly of claims 3-6 characterized by said first module (18) and said end-cap (50) being molded members composed of a polymeric material. 10
8. The filter assembly of claim 4 characterized by said weld providing a fluid tight connection with respect to said first module cavity (56). 15
9. A filter base assembly (12) having an inlet (27), an outlet (33), and first (24) and second (26) conduits in fluid communication with the inlet (27) and outlet (33), respectively, characterized by: 20
 - a first module (18) composed of polymeric material and comprising a first plate (38);
 - a second module (20) comprising a second plate (36) defining an aperture (48) for receiving the first (24) and second (26) conduits, said first module first plate (38) being mounted to said second module second plate (36); and 25
 - an end-cap (50) composed of a polymeric material mounted to said first module (18), said end-cap (50) at least partially defining a cavity (56). 30
10. The filter base assembly (12) of claim 9 characterized by said second module (20) being composed of cast metal. 35
11. The filter base assembly of claims 9 and 10 characterized by said end-cap (50) being sonically welded to said first module (18). 40
12. The filter base assembly of claims 9-11 characterized by said first module (18) further comprising locating means (30) for positioning the first (24) and second (26) conduits within said second module aperture (48). 45

50

55




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6



4-11-74

1-1-75



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) Publication number:

0 657 201 A3

(12)

EUROPEAN PATENT APPLICATION

(21) Application number: **94119522.4**

(51) Int. Cl.⁶: **B01D 35/30**

(22) Date of filing: **09.12.94**

(30) Priority: **13.12.93 US 166226**

(43) Date of publication of application:
14.06.95 Bulletin 95/24

(84) Designated Contracting States:
DE ES FR GB IT

(88) Date of deferred publication of the search report:
15.11.95 Bulletin 95/46


(71) Applicant: **STANADYNE AUTOMOTIVE CORP.**
92 Deerfield Road
Windsor
Connecticut 06095 (US)

(72) Inventor: **Janik, Leon P.**
879 North Street
Suffield,
Connecticut 06078 (US)
Inventor: **Maxwell, M. Craig**
8 Forest Drive
Colchester,
Connecticut 06415 (US)

(74) Representative: **Glawe, Delfs, Moll & Partner**
Patentanwälte
Liebherrstrasse 20
D-80538 München (DE)

(54) **Module for filter assembly base.**

(57) A filter assembly (10) employs a base (12) which mounts a disposable filter element cartridge (14). The cartridge (14) includes either a single stage or a dual stage filter system. The base (12) has custom and generic (20) structural members. Variations in base design are accommodated in the custom member, the generic member (20) having a generic design. The custom member is molded from polymeric material and requires no additional machining or treatment prior to use. This eliminates filter model specific shop fixtures and jigs, reducing costs and providing greater flexibility.



EP 0 657 201 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 94 11 9522

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
A	EP-A-0 529 782 (STANADYNE AUTOMOTIVE CORP) - * figure 1 *	1,9	B01D35/30
A	DE-A-23 60 539 (KORDON CORP) * page 3, line 22 - line 27; figure 1 *	1,9	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			B01D
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 14 September 1995	Examiner De Paepe, P
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☐ BLACK BORDERS

☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES

☒ FADED TEXT OR DRAWING

☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING

☐ SKEWED/SLANTED IMAGES

☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS

☐ GRAY SCALE DOCUMENTS

☐ LINES OR MARKS ON ORIGINAL DOCUMENT

☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)